

NIGHT VISION GOGGLES

NVG7-2

Lightweight, rugged and a top notch performer the NVG7 is an exceptional choice for hands-free usage. This model features high resolution image intensifier, autobrightness, and bright source shut-off. NVG7 goggles also have a built-in IR for total darkness with indicator ON light within the FOV and flip. One CR123A, case and manual are included. ATN NVG7 is an excellent choice for hands-free night vision applications.

ACCESSORIES



TUBE SPECIFICATIONS

| HIGH QUALITY 2 GEN IMAGE INTENSIF | IER TUBE |
|--|------------------------------|
| DESCRIPTION | Standard |
| GENERATION | 2+ |
| PHOTOCATHODE TYPE | Multi - Alkali |
| RESOLUTION, Ip/mm* | 40-45 |
| SIGNAL TO NOISE RATIO* | 12-20 |
| FIGURE OF MERIT | <1250 |
| MTTF - MEAN TIME BEFORE FAILURE, hours | 5,000 |
| EXPORT | N/A for Export |
| * Considerations are provided for informational nursesses or | ulu. A atual walung manusami |

* Specifications are provided for informational purposes only. Actual values may vary

- Lightweight, compact rugged Goggle system
- I Multi-purpose: Hand-held, head-mounted or helmet-mounted
- **■** Comfortable, flip-up headgear
- Multi-coated all-glass optics
- **■** Wide angle infrared illuminator
- Head Mount Included
- Adjustable Interpupillary Distance
- Optional 3x, 5x and 8x lenses available
- Water and fog resistant
- Limited Two-Year Warranty

SPECIFICATIONS

| Magnification | 1x |
|------------------------------|------------------------------------|
| Lens System | F1:1.2, 26 mm |
| Proshield Lens Coating | Yes |
| FOV | 40° |
| Range of Focus | 0.25 m to infinity |
| Diopter Adjustment | -6 to +5 |
| Controls | Direct |
| Automatic Brightness Control | Yes |
| Bright Light Cut-off | Yes |
| Automatic Shut-off System | Yes |
| Infrared Illuminator | Yes |
| IR Indicator | Yes |
| Power Supply | 1x3 V CR123A type battery |
| Battery Life | 50 hrs |
| Environmental Rating | Waterproof |
| Operating Temperature | -40 to +50 °C |
| Storage Temperature | -50 to +70 °C |
| Dimensions | 160 x 150 x 75 mm / 6.3" x 6" x 3" |
| Weight | 0.5 kg / 1.1 lbs |
| Warranty | 2 years |

Export Warning: These products are subject to one or more of the export control laws and regulations of the U.S. Government. Pending the model these products are under the control jurisdiction of either the US Department of State or the US Bureau of Industry and Security US Department of Commerce. Export without proper licensing or consent is strictly prohibited.