

The PS-15 is a compact, lightweight dual night vision goggle system. It utilizes two high performance image intensifier tubes to provide extremely clear and crisp images under the darkest conditions. This dual tube design provides increased depth perception and outstanding clarity. A built-in IR lets the user easily read a map and function in a total darkness environment.



- Dual goggle/binocular
- Hands-Free use
- Comfortable flip-up headgear
- Lightweight, Compact
- Optional 3x Afocal lenses to make into a binocular
- Waterproof
- Limited Two-Year Warranty

SPECIFICATIONS

Magnification	1x	
Lens System	F1.2, 27 mm	
Proshield Lens Coating	Yes 40°	
FOV		
Range of Focus	0.25 m to infinity	
Diopter Adjustment	-6 to +2	
Controls	Direct	
Automatic Brightness Control	Yes	
Bright Light Cut-off	Yes	
Automatic Shut-off System	Yes	
Infrared Illuminator	Yes (Built-in with flood lens)	
IR Indicator	Yes (in FOV)	
Power Supply	1x1.5 V AA type battery or 1x3 V CR123A type battery	
Battery Life	20-40 hrs	
Environmental Rating	Waterproof	
MIL-STD-810	Complies	
Operating Temperature	-40 to +50 °C	
Storage Temperature	-50 to +70 °C	
Dimensions	120x114x69 mm / 4.7"x4.5"x2.7"	
Weight	0.7 kg / 1.54 lbs	

TUBE SPECIFICATIONS

HIGH QUALITY 3 GEN IMAGE INTENSIFIER TUBE

DESCRIPTION	Standard	
GENERATION	3	
PHOTOCATHODE TYPE	GaAs	
RESOLUTION, Ip/mm*	64	
SIGNAL TO NOISE RATIO*	22 Typical	
FIGURE OF MERIT	1600 Typical	
MTTF - MEAN TIME BEFORE FAILURE, hours	10,000	
EXPORT	N/A for Export	
* Specifications are provided for informational purposes only. Actual values may vary		

Export Warning: These products are subject to one or more of the export control laws and regulations of the U.S. Government. Pending the model these products are under the control jurisdiction of either the US Department of State or the US Bureau of Industry and Security US Department of Commerce. Export without proper licensing or consent is strictly prohibited.

1341 San Mateo Ave, South San Francisco, CA 94080.

www.atncorp.com

e-mail: sales@atncorp.com, info@atncorp.com

Tel: 800-910-2862, 650-989-5100, fax: 650-875-0129