

## **TECHNICAL SPECIFICATIONS**

Riflescope Digisight LRF N850

Camera resolution, pixels (EIA)	500x582
Display type	OLED
Display Resolution, pix	VGA 640x480
Display diagonal, inch	0.31
Built-In video recorder availabil-	no
ity	110
Video IN/OUT availability	no / yes
Pin type of video input/output	RCA
Magnification	4.5 (optical) / 9 (zoom)
Lens diameter, mm	50
Field of view,*, horizontal	5 (on 4.5x) / 2.4 (on 9x)
Field of view, m@100m	8.7 / 4.2
Minimum focusing distance	5.5
Eye relief, mm	67
Exit pupil, mm	6
Diopter adjustment, dptr	-4 + 4
Focusing type of distance	internal
Resolution, lines per mm	> 55
Emitter	Laser
IR Wavelenght, nm	780
Equivalent IR power, mW	75 / 100 / 125
Beam divergence, degree	9.17
Range of detection, yd/m (object	650 / 600
1.7m high, illuminatuin level 0.05	
lux w/ 1/4moon)	(50.1/00
Measurement range, yd/m	450 / 400
Accuracy of range mesurement, yd/m	+/-1
Power supply	4 ÷ 6.3
Battery Type	4xAA
Battery life(w/out IR), hour	4
Battery life(w/IR), hour	2.5 - 3.5
External power supply	DC 9 ÷ 15V / 3W
Windage & elevation, 1 click	13 /13
(H/V), mm @100m	
Reticle color	Black w/ switchable red/green center
Number of preloaded reticles	13
Reticle type	Black/white w/ switcheable red/green
	center
Lens material	Glass



## **INCLUDED ACCESSORIES**

- Riflescope digisight LRF N850
- Wireless remote control
- Mount
- 3 Screws
- Hex-nut Wrench
- Carrying case
- User Manual
- Cleaning cloth

## **TECHNICAL SPECIFICATIONS**

Riflescope Digisight LRF N850

Body Material	Glass-nylon composite
Type of mount for attachment of additional accesspries	weaver
Operating temp, *C/*F	-25 + 50 / -13 +122
Level of protection (acc. to IEC 60529)	IP44 ( water resistant )
Nitrogen purged, yes/no	no
Waterproof, yes/no	no
Remote control	Wireless
Shockresistance on rifled weap- on	6000
Mounting brackets on weapon	weaver
Length, mm	340
Width, mm	112
Height, mm	94
Weight (W/out batteries), oz	38.8